

F2-100

F2-100 super slim sport stadium screen solution

- . Front service modules design
- . Dual backup for power supply and receiving card
- . Emergency Exit design
- . Air pressure bar design
- . Certificates



Size



Product specifications

Product	F2-100
Pixel Pitch (mm)	10
Brightness (Nit)	6000
Dimension (mm)	1280 × 960
Refresh Rate (Hz)	≥ 2880
Color Depth (Bit)	14
IP Grade	IP65/IP54
Ave.Power Consumption (W/m ²)	258
Weight (Kg)	45

F2-100

Front service modules design

- Aluminum Die casting LED modules, better heat dissipation function, up to 50% dissipation capacity than others
- High protection grade on LED Module, protection grade IP65/IP54 (front/back)
- Front service module design, easy for daily maintenance and saving time

Dual backup for power supply and receiving card



X2



X2

Air pressure bar design

- Buffer function back support for better protection on both LEDs and athletes
- Angle adjustable: 70-90 degree, 5 degree each step, to achieve better view angle
- Air pressure bar removable, convenient for fixed application



Main application area



Basketball court



Soccer field



Football court



Certificates



CE-LVD



CE-EMC



FCC



ETL

Emergency exit design

Fast lock system and return pulley underneath support to remove one cabinet easily for exit in case of emergency

